



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	350 bar
	blocked control port (dead headed)
	0,11 - 0,16 L/min.
-	5
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

: • O 1 0.75 in. (19 mm)

CONFIGURATION OPTIONS

Model Code Example: PBDFLAN

(L)	(A)	(N)	MATERIAL/COATING
L	A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	N	Standard Material/Coating
C -	B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	V	/AP
K	D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)		/LH -
	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
	G 60 - 3000 psi (4 - 210 bar), 200 psi (14 bar)		
	K 75 - 1500 psi (5 - 105 bar), 200 psi (14 bar)		
	N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)		
	P 40 - 400 psi (2,8 - 28 bar), 200 psi (14 bar)		
	Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)		
	W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)		