



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-11A
	1
	40 L/min.
	350 bar
	blocked control port (dead headed)
	0,11 - 0,16 L/min.
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.16 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

: • 0 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: PBDFLAN

	(L)	(A)	(N)	MATERIAL/COATING
L		A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	N	Standard Material/Coating
C	-		V	/AP
K		B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)		/LH -
		D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)		
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
		G 60 - 3000 psi (4 - 210 bar), 200 psi (14 bar)		
		K 75 - 1500 psi (5 - 105 bar), 200 psi (14 bar)		
		N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)		
		P 40 - 400 psi (2,8 - 28 bar), 200 psi (14 bar)		
		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)		
		W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)		

TECHNICAL FEATURES

-
- 3 / 3
- 1 2
- /
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- 3 1:1 5000 psi 350 bar
- /
- W Y W Y
- /AP
- Sun /

PERFORMANCE CURVES



