



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--|------------------------------------|
| Maximum Operating Pressure | 350 bar |
| Control Pilot Flow | 0,11 - 0,16 L/min. |
| Factory Pressure Settings Established at | blocked control port (dead headed) |
| Adjustment - No. of CW Turns from Min. to Max. setting | 5 |
| Locknut Hex Size | 15 mm |
| Locknut Torque | 9 - 10 Nm |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |

CONFIGURATION OPTIONS

Model Code Example: PBDFLANN

| CONTROL | (L) | ADJUSTMENT RANGE | (A) | SEAL MATERIAL | (N) | MATERIAL/COATING |
|----------------------------------|-----|--|-----|---------------|-----|---------------------------------|
| L Standard Screw Adjustment | | A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting | | N Buna-N | | Standard Material/Coating |
| C Tamper Resistant - Factory Set | | B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting | | V Viton | | /AP Stainless Steel, Passivated |
| K manilla | | C 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar) Standard Setting | | | | /LH Mild Steel, Zinc-Nickel |
| | | D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting | | | | |
| | | E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting | | | | |
| | | N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting | | | | |