



CONFIGURATION

L	
N	60 - 800 psi (4 - 55 bar), 200 psi (14 bar)
N	
	Material/Coating

TECHNICAL DATA

	350 bar
	blocked control port (dead headed)
	0,11 - 0,16 L/min.
-	5
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

: • O 1 0.75 in. (19 mm)

CONFIGURATION OPTIONS

Model Code Example: PBDFLNN

(L)	(N)	(N)	MATERIAL/COATING	(/LH)
L	N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	N	/LH -	
C -		V	/AP	
K	A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) G 60 - 3000 psi (4 - 210 bar), 200 psi (14 bar) K 75 - 1500 psi (5 - 105 bar), 200 psi (14 bar) P 40 - 400 psi (2,8 - 28 bar), 200 psi (14 bar) Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)			Standard Material/Coating