



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-2A
	2
	80 L/min.
	350 bar
	blocked control port (dead headed)
	0,16 - 0,25 L/min.
	5
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.29 kg.
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

: • : A B 3000 psi (210 bar) N Q 2000 psi (140 bar) W 5000 psi (350 bar)
 • O 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: PBFBLNN

	(L)	(N)	(N)	MATERIAL/COATING
L	N	N	N	Standard Material/Coating
J	A	V	V	/AP
O	B			/LH
W	C			
	D			
	Q			
	W			

TECHNICAL FEATURES

- 3 / / 3
- 1 2
- /
- 150
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- 3 1:1 5000 psi 350 bar
- /
- W Y W Y
- EPDM
- Sun /

PERFORMANCE CURVES



