



CONFIGURATION

L	
N	60 - 800 psi (4 - 55 bar), 200 psi (14 bar)
N	
	Material/Coating

TECHNICAL DATA

NOTE:

	T-2A	DATA
	2	MAY
	80 L/min.	VARY
	blocked control port (dead headed)	BY
	0,16 - 0,25 L/min.	
-	5	
	28,6 mm	
	61 - 68 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	0.29 kg.	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	EPDM: 990-202-014	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-202-006	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	EPDM: 990-202-014	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-202-006	

CONFIGURATION. SEE CONFIGURATION SECTION.

: • O 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: PBFFLNN

	(L)	(N)	(N) MATERIAL/COATING
L		N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	N Standard Material/Coating
C -			V /LH -
K		A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)	

TECHNICAL FEATURES

-
- EPDM
- 3 / 3
- 1 2
- /
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- 3 1:1 5000 psi 350 bar
- /
- Sun /

PERFORMANCE CURVES

