



CONFIGURATION

L	
A	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)
N	Material/Coating

TECHNICAL DATA

	350 bar
	blocked control port (dead headed)
	0,25 - 0,33 L/min.
-	5
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	EPDM: 990-017-014
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	EPDM: 990-017-014
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

: • : A B 3000 psi (210 bar) N Q 2000 psi (140 bar) W 5000 psi (350 bar)

CONFIGURATION OPTIONS

Model Code Example: PBHBLAN

(L)	(A)	(N)	MATERIAL/COATING	(/LH)
L	A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	N	/LH	-
W	B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	E EPDM	/AP	Standard Material/Coating
	C 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar)	V		
	D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)			
	N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)			
	Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)			
	W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)			