



CONFIGURATION

L	
A	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)
N	
	Material/Coating

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-17A
	3
	160 L/min.
	350 bar
	blocked control port (dead headed)
	0,25 - 0,33 L/min.
	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.57 kg.
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	EPDM: 990-017-014
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	EPDM: 990-017-014
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

: A B 3000 psi (210 bar) N Q 2000 psi (140 bar) W 5000 psi (350 bar)

OPTION SELECTION EXAMPLE: PBHBLAN

	(L)	(A)	(N)	MATERIAL/COATING	(/LH)
L	A	N	/LH	-	
W	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar) 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)	E EPDM V	/AP	Standard Material/Coating	

TECHNICAL FEATURES

- 3 / / 3
- 1 2
- /
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- 3 1:1 5000 psi 350 bar
- /
- W Y W Y
- EPDM
- Sun /

PERFORMANCE CURVES



