



**CONFIGURATION**

L	
N	60 - 800 psi (4 - 55 bar), 200 psi (14 bar)
N	
N	Material/Coating

**TECHNICAL DATA**

NOTE:

	T-17A	DATA
	3	MAY
	160 L/min.	VARY
	350 bar	BY
	blocked control port (dead headed)	
	0,25 - 0,33 L/min.	
-	5	
	31,8 mm	
	203 - 217 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	0.57 kg.	
Seal kit - Cartridge	Buna: 990-017-007	
Seal kit - Cartridge	EPDM: 990-017-014	
Seal kit - Cartridge	Polyurethane: 990-017-002	
Seal kit - Cartridge	Viton: 990-017-006	
Seal kit - Cartridge	Buna: 990-017-007	
Seal kit - Cartridge	EPDM: 990-017-014	
Seal kit - Cartridge	Polyurethane: 990-017-002	
Seal kit - Cartridge	Viton: 990-017-006	

CONFIGURATION. SEE CONFIGURATION SECTION.

: • : A B 3000 psi (210 bar) N Q 2000 psi (140 bar) W 5000 psi (350 bar)

# OPTION SELECTION EXAMPLE: PBHBLNN

	(L)	(N)	(N)	MATERIAL/COATING	(/LH)
<b>L</b>		<b>N</b> 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	<b>N</b>	<b>/LH</b> -	
<b>C</b>	-		<b>E</b> EPDM	<b>/AP</b>	
<b>K</b>		<b>A</b> 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	<b>V</b>		Standard Material/Coating
<b>W</b>		<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)			
<b>Y</b>		<b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)			
		<b>W</b> 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)			

## TECHNICAL FEATURES

- 3 / 3
- 1 2
- /
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- 3 1:1 5000 psi 350 bar
- /
- W Y W Y
- EPDM
- Sun /

## PERFORMANCE CURVES

