



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|------------------------------------|
| | T-17A |
| | 3 |
| | 160 L/min. |
| | 350 bar |
| | T-8A |
| | blocked control port (dead headed) |
| | 0,25 - 0,33 L/min. |
| | 31,8 mm |
| | 203 - 217 Nm |
| | 0.46 kg. |
| Seal kit - Cartridge | Buna: 990-017-007 |
| Seal kit - Cartridge | EPDM: 990-017-014 |
| Seal kit - Cartridge | Polyurethane: 990-017-002 |
| Seal kit - Cartridge | Viton: 990-017-006 |
| Seal kit - Cartridge | Buna: 990-017-007 |
| Seal kit - Cartridge | EPDM: 990-017-014 |
| Seal kit - Cartridge | Polyurethane: 990-017-002 |
| Seal kit - Cartridge | Viton: 990-017-006 |

OPTION SELECTION EXAMPLE: PBHB8WN

(W)

(N)

W 100 psi (7 bar)

D 25 psi (1,7 bar)

N

E EPDM

V

TECHNICAL FEATURES

- 3 / 3
- 1 2
- 150
- /
- 3 1:1 5000 psi 350 bar
- D 2000 psi (140 bar) W 5000 psi (350 bar)
- -8 T-8A
- -8 T-8A
- EPDM
- Sun /

PERFORMANCE CURVES

