



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

CONFIGURATION OPTIONS

Model Code Example: PBHFLAN

CONTROL

(L)

ADJUSTMENT RANGE

(A)

SEAL MATERIAL

(N)

L Standard Screw Adjustment

C Tamper Resistant - Factory Set

W Hex Wrench Adjustment

Y manilla de tres agarres

A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)
Standard Setting

B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)
Standard Setting

C 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar)
Standard Setting

D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)
Standard Setting

E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)
Standard Setting

N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)
Standard Setting

Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)
Standard Setting

W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)
Standard Setting

N Buna-N

V Viton