



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--|------------------------------------|
| Maximum Operating Pressure | 350 bar |
| Control Pilot Flow | 0,11 - 0,16 L/min. |
| Factory Pressure Settings Established at | blocked control port (dead headed) |
| Adjustment - No. of CW Turns from Min. to Max. setting | 5 |
| Locknut Hex Size | 12,7 mm |
| Locknut Torque | 9 - 10 Nm |
| Seal kit - Cartridge | Buna: 990-163-007 |
| Seal kit - Cartridge | EPDM: 990-163-014 |
| Seal kit - Cartridge | Polyurethane: 990-163-002 |
| Seal kit - Cartridge | Viton: 990-163-006 |
| Seal kit - Cartridge | Buna: 990-163-007 |
| Seal kit - Cartridge | EPDM: 990-163-014 |
| Seal kit - Cartridge | Polyurethane: 990-163-002 |
| Seal kit - Cartridge | Viton: 990-163-006 |

CONFIGURATION OPTIONS

Model Code Example: PPBLAN

| CONTROL | (L) | ADJUSTMENT RANGE | (A) | SEAL MATERIAL | (N) | MATERIAL/COATING |
|----------------------------------|-----|---|-----|---------------|-----|---------------------------------|
| L Standard Screw Adjustment | | A 75 - 3000 psi (5 - 210 bar), 200 psi (14 bar) Standard Setting | | N Buna-N | | Standard Material/Coating |
| C Tamper Resistant - Factory Set | | B 75 - 1500 psi (5 - 105 bar), 200 psi (14 bar) Standard Setting | | E EPDM | | /AP Stainless Steel, Passivated |
| K manilla | | N 75 - 800 psi (5 - 55 bar), 200 psi (14 bar) Standard Setting | | V Viton | | /LH Mild Steel, Zinc-Nickel |
| | | Q 75 - 400 psi (5 - 28 bar), 200 psi (14 bar) Standard Setting | | | | |
| | | W 100 - 4500 psi (7 - 315 bar), 200 psi (14 bar) Standard Setting | | | | |