



CONFIGURATION

L	Control	Standard Screw Adjustment
A	Adjustment Range	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting
N	Seal Material	Buna-N
	Material/Coating	

TECHNICAL DATA

NOTE:

cavidad	T-11A	DATA
Series	1	MAY
Capacity	40 L/min.	VARY
Maximum Operating Pressure	350 bar	BY
Control Pilot Flow	0,11 - 0,16 L/min.	
Factory Pressure Settings Established at	blocked control port (dead headed)	
Adjustment - No. of CW Turns from Min. to Max. setting	5	
Valve Hex Size	22,2 mm	
Valve Installation Torque	41 - 47 Nm	
Adjustment Screw Internal Hex Size	4 mm	
Locknut Hex Size	15 mm	
Locknut Torque	9 - 10 Nm	
Model Weight	0.15 kg.	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	EPDM: 990-011-014	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	EPDM: 990-011-014	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: PPDBLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
L	Standard Screw Adjustment	A	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting	N	Buna-N	/LH	Mild Steel, Zinc-Nickel
C	Tamper Resistant - Factory Set	B	50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting	V	Viton	/AP	Stainless Steel, Passivated
K	manilla	C	150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar) Standard Setting				Standard Material/Coating
		D	25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting				
		E	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				
		N	60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting				

PERFORMANCE CURVES

