



CONFIGURATION

L	
A	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)
N	
Material/Coating	

TECHNICAL DATA

NOTE:
DATA
MAY
VARY
BY

	T-11A
	1
	40 L/min.
	350 bar
	blocked control port (dead headed)
	0,11 - 0,16 L/min.
	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.15 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

CONFIGURATION. SEE
CONFIGURATION SECTION.

- : A B 3000 psi (210 bar) N Q 2000 psi (140 bar) W 5000 psi (350 bar)
- O 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: PPDBLAN

	(L)	(A)	(N)	MATERIAL/COATING	(/LH)
L		A	N	/LH	-
O			V	/AP	
W		B			Standard Material/Coating
		C			
		D			
		N			
		Q			
		W			

TECHNICAL FEATURES

- 3 / 3
- 1 2
- /
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- 3 1:1 5000 psi 350 bar
- /
- W Y W Y
- EPDM
- Sun /

PERFORMANCE CURVES



