



CONFIGURATION

L	Control	Standard Screw Adjustment
A	Adjustment Range	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting
N	Seal Material	Buna-N
	Material/Coating	

TECHNICAL DATA

NOTE:
DATA
MAY
VARY
BY

cavidad	T-2A
Series	2
Capacity	80 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,16 - 0,25 L/min.
Factory Pressure Settings Established at	blocked control port (dead headed)
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.27 kg.
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: PPFBLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
L	Standard Screw Adjustment	A	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting	N	Buna-N	/LH	Mild Steel, Zinc-Nickel
C	Tamper Resistant - Factory Set	B	50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting	E	EPDM	/AP	Stainless Steel, Passivated
K	manilla	D	25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting	V	Viton		Standard Material/Coating
		E	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				
		N	60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting				
		S	25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar) Standard Setting				

PERFORMANCE CURVES

