



2 1 1 3

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-2A
	2
	80 L/min.
	350 bar
	blocked control port (dead headed)
	0,16 - 0,25 L/min.
	5
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0,30 kg
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

: • : A B 3000 psi (210 bar) N Q 2000 psi (140 bar) W 5000 psi (350 bar)
• O 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: PPFBLANN

	(L)	(A)	(N)	MATERIAL/COATING
L	A	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	N	Standard Material/Coating
C	B	50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	E	/AP
K	N	60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	V	/LH
M	Q	60 - 400 psi (4 - 28 bar), 200 psi (14 bar)		
Q	W	150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)		
W				
Y				

TECHNICAL FEATURES

- 3 1:1 3000 psi 210 bar
- 3 3000 psi (210 bar)
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- /
- W Y W Y
- EPDM
- 3 / / 3
- 1 2
- /
- Sun /

PERFORMANCE CURVES

