



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

CONFIGURATION OPTIONS

Model Code Example: PPFFLAN

CONTROL

(L)

ADJUSTMENT RANGE

(A)

SEAL MATERIAL

(N)

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)
L Standard Screw Adjustment	A	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting	N	Buna-N	
C Tamper Resistant - Factory Set	B	50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting	V	Viton	
	D	25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting			
	E	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting			
	N	60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting			
	Q	60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting			
	W	100 - 5000 psi (7 - 350 bar), 200 psi (14 bar) Standard Setting			