



**CONFIGURATION**

L	
N	60 - 800 psi (4 - 55 bar), 200 psi (14 bar)
N	

**TECHNICAL DATA**

NOTE:

	T-2A	DATA
	2	MAY
	80 L/min.	VARY
	350 bar	BY
	blocked control port (dead headed)	
	0,16 - 0,25 L/min.	
-	5	
	28,6 mm	
	61 - 68 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	0.27 kg.	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-202-006	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-202-006	

CONFIGURATION. SEE CONFIGURATION SECTION.

: • O 1 0.75 in. (19 mm)

# OPTION SELECTION EXAMPLE: PPFFLNN

(L)

(N)

(N)

<b>L</b>	<b>N</b> 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	<b>N</b>
<b>C</b> -	<b>A</b> 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	<b>V</b>
<b>K</b>	<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	
	<b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)	
	<b>W</b> 100 - 5000 psi (7 - 350 bar), 200 psi (14 bar)	

## TECHNICAL FEATURES

- 
- 3 3000 psi (210 bar)
- 3 1:1 3000 psi 210 bar
- /
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- W Y W Y
- 3 / / 3
- 1 2
- /
- Sun /

## PERFORMANCE CURVES

