



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

CONFIGURATION OPTIONS

Model Code Example: **PPHFLAN**

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)
L Standard Screw Adjustment		A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting		N Buna-N	
C Tamper Resistant - Factory Set		B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting		V Viton	
		C 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar) Standard Setting			
		D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting			
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting			
		N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting			
		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting			
		W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) Standard Setting			