



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-17A
Series	3
Capacity	160 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,25 - 0,33 L/min.
Factory Pressure Settings Established at	blocked control port (dead headed)
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.56 kg.
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

OPTION SELECTION EXAMPLE: PPHFLAN

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
L Standard Screw Adjustment	<p>A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting</p> <p>B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting</p> <p>D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting</p> <p>N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting</p> <p>W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) Standard Setting</p>	<p>N Buna-N</p> <p>V Viton</p>	

PERFORMANCE CURVES

