



CONFIGURATION

L	
N	60 - 800 psi (4 - 55 bar), 200 psi (14 bar)
N	

TECHNICAL DATA

NOTE:

	T-17A	DATA
	3	MAY
	160 L/min.	VAR
	350 bar	BY
	blocked control port (dead headed)	
	0,25 - 0,33 L/min.	
	5	
	31,8 mm	
	203 - 217 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	0.56 kg.	
Seal kit - Cartridge	Buna: 990-017-007	
Seal kit - Cartridge	Polyurethane: 990-017-002	
Seal kit - Cartridge	Viton: 990-017-006	
Seal kit - Cartridge	Buna: 990-017-007	
Seal kit - Cartridge	Polyurethane: 990-017-002	
Seal kit - Cartridge	Viton: 990-017-006	

CONFIGURATION. SEE CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: PPHFLNN

(L)

(N)

(N)

L	N	N
C -	A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	V
K	B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	
Q	C 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar)	
	D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)	
	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)	
	H 30 - 3000 psi (2 - 210 bar), 200 psi (14 bar)	
	Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)	
	W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)	

TECHNICAL FEATURES

-
- 3 3000 psi (210 bar)
- 3 1:1 3000 psi 210 bar
- /
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- 3 / 3
- 1 2
- /
- Sun /

PERFORMANCE CURVES

