



CONFIGURATION

L	
N	60 - 800 psi (4 - 55 bar), 200 psi (14 bar)
N	
	Material/Coating

TECHNICAL DATA

NOTE:

	T-19A	DATA
	4	MAY
	320 L/min.	VARY
	350 bar	BY
	blocked control port (dead headed)	
	0,25 - 0,33 L/min.	
	5	
	41,3 mm	
	474 - 508 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	1.29 kg.	
Seal kit - Cartridge	Buna: 990-019-007	
Seal kit - Cartridge	Polyurethane: 990-019-002	
Seal kit - Cartridge	Viton: 990-019-006	
Seal kit - Cartridge	Buna: 990-019-007	
Seal kit - Cartridge	Polyurethane: 990-019-002	
Seal kit - Cartridge	Viton: 990-019-006	

: • : A B 3000 psi (210 bar) N Q 2000 psi (140 bar) W 5000 psi (350 bar)

CONFIGURATION. SEE CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: PPJBLNN

	(L)	(N)	(N)	MATERIAL/COATING	(/LH)
L		N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	N	/LH -	
C	-		E EPDM	/AP	
K		A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	V		Standard Material/Coating
W		B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)			
Y		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)			
		W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)			

TECHNICAL FEATURES

- 3 1:1 3000 psi 210 bar
- 3 3000 psi (210 bar)
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- /
- 3 / 3
- 1 2
- /
- Sun /

PERFORMANCE CURVES

