



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006

**CONFIGURATION OPTIONS**

Model Code Example: **PPJFLAN**

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)
<b>L</b> Standard Screw Adjustment		<b>A</b> 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting		<b>N</b> Buna-N	
<b>C</b> Tamper Resistant - Factory Set		<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting		<b>V</b> Viton	
		<b>D</b> 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting			
		<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting			
		<b>N</b> 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting			
		<b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting			
		<b>W</b> 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) Standard Setting			