



2 1 1 3

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-163A
	0
	20 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min.
	0.25 gpm
	7
	19,1 mm
	27 - 33 Nm
	12,7 mm
	9 - 10 Nm
	0,15 kg
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	EPDM: 990-163-014
Seal kit - Cartridge	Viton: 990-163-006

## OPTION SELECTION EXAMPLE: PRBBLANV

	(L)	(A)	(V)	MATERIAL/COATING
<b>L</b>	-	<b>A</b> 500 - 3000 psi (35 - 210 bar), 700 psi (50 bar)	<b>V</b>	Standard Material/Coating
<b>C</b>	-	<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	<b>E</b> EPDM	/AP
		<b>D</b> 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)	<b>N</b>	/LH -
		<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
		<b>S</b> 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar)		
		<b>W</b> 750 - 4500 psi (50 - 315 bar), 1000 psi (70 bar)		

### TECHNICAL FEATURES

- 3 / 3
- 1 2
- 5000 psi (350 bar)
- 
- 
- 
- 
- 5%
- 3 1:1 5000 psi 350 bar
- 3 2000 psi (140 bar)
- W Y W Y
- EPDM
- Sun /

### PERFORMANCE CURVES



