



2

1

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|--------------------|
| | T-163A |
| | 0 |
| | 20 L/min. |
| | 350 bar |
| 110 SUS (24 cSt) | 330 cc/min. |
| | 0.25 gpm |
| | 7 |
| | 19,1 mm |
| | 27 - 33 Nm |
| | 4 mm |
| | 12,7 mm |
| | 9 - 10 Nm |
| | 0,15 kg |
| Seal kit - Cartridge | Buna: 990-163-007 |
| Seal kit - Cartridge | Viton: 990-163-006 |

OPTION SELECTION EXAMPLE: PRBCLANV

(L)

(A)

(V)

| | | |
|------------|---|---------------|
| L | A 500 - 3000 psi (35 - 210 bar), 700 psi (50 bar) | V |
| C - | B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) | E EPDM |
| | D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) | N |
| | E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) | |
| | S 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar) | |
| | W 750 - 4500 psi (50 - 315 bar), 1000 psi (70 bar) | |

TECHNICAL FEATURES

- 3 1:1 3000 psi 210 bar
- 3 2000 psi (140 bar)
- 0.1 gpm(0,4 L/)
- 3 / / 3
- 1 2
- 5000 psi (350 bar)
-
-
- Sun /

PERFORMANCE CURVES

