



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-163A
	0
	20 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min.
	0.25 gpm
-	5
	19,1 mm
	27 - 33 Nm
	4 mm
	12,7 mm
	9 - 10 Nm
	0.14 kg.
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	EPDM: 990-163-014
Seal kit - Cartridge	Viton: 990-163-006
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	EPDM: 990-163-014
Seal kit - Cartridge	Viton: 990-163-006

# OPTION SELECTION EXAMPLE: PRBRLAN

	(L)	(A)	(N)	MATERIAL/COATING
<b>L</b>	<b>A</b>	500 - 3000 psi (35 - 210 bar), 700 psi (50 bar)	<b>N</b>	Standard Material/Coating
	<b>B</b>	50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	<b>E</b>	/AP
	<b>D</b>	25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)	<b>V</b>	/LH
	<b>W</b>	750 - 4500 psi (50 - 315 bar), 1000 psi (70 bar)		

## TECHNICAL FEATURES

- 
- PR\*R LP\*C
- EPDM
- 1 2
- 5000 psi (350 bar)
- 
- 
- 3 1:1 5000 psi 350 bar
- 3 2000 psi (140 bar)
- Sun /

## PERFORMANCE CURVES

