



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Series	1
Capacity	40 L/min.
Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	0.25 gpm
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.20 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

OPTION SELECTION EXAMPLE: PRDBLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
L		A	500 - 3000 psi (35 - 210 bar), 700 psi (50 bar) Standard Setting	N	Buna-N	Standard Material/Coating
C		B	50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting	E	EPDM	/AP Stainless Steel, Passivated
W		D	25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting	V	Viton	/LH Mild Steel, Zinc-Nickel
Y		E	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting			
		W	750 - 4500 psi (50 - 315 bar), 1000 psi (70 bar) Standard Setting			

PERFORMANCE CURVES

