



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-11A
	1
	40 L/min.
	350 bar
110 SUS (24 cSt)	330 cc/min.
	0.25 gpm
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.20 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

: • 0 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: PRDCLAN

	(L)	(A)	(N)	MATERIAL/COATING
L		A 500 - 3000 psi (35 - 210 bar), 700 psi (50 bar)	N	Standard Material/Coating
C	-		E EPDM	/AP
K		B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	V	
O		D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)		
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
		S 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar)		
		W 750 - 4500 psi (50 - 315 bar), 1000 psi (70 bar)		

TECHNICAL FEATURES

- 0.1 gpm(0,4 L/)
- EPDM
- 3 / / 3
- 1 2
- 5000 psi (350 bar)
-
-
- 3 1:1 5000 psi 350 bar
- 3 2000 psi (140 bar)
- Sun /

PERFORMANCE CURVES

