



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-511-007
Seal kit - Cartridge	Viton: 990-511-006

**CONFIGURATION OPTIONS**

**Model Code Example: PRDMXDN**

CONTROL	(X)	ADJUSTMENT RANGE	(D)	SEAL MATERIAL	(N)	BOBINA
<b>X</b> No Manual Override		<b>D</b> 400 - 200 psi (14 - 28 bar)		<b>N</b> Buna-N		No coil
		<b>B</b> 1000 - 400 psi (28 - 70 bar)		<b>V</b> Viton		<b>224NX01</b> DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
		<b>E</b> 200 - 100 psi (7 - 14 bar)				<b>224NX02</b> DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
		<b>S</b> 100 - 10 psi (0,7 - 7 bar)				<b>912NX01</b> Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						<b>912NX02</b> Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
						<b>924NX01</b> Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						<b>924NX02</b> Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver