



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-511-007
Seal kit - Cartridge	Viton: 990-511-006

CONFIGURATION OPTIONS

Model Code Example: PRDNXDN

CONTROL	(X)	ADJUSTMENT RANGE	(D)	SEAL MATERIAL	(N)	BOBINA
X No Manual Override		D 400 - 200 psi (14 - 28 bar)		N Buna-N		No coil
		B 1000 - 400 psi (28 - 70 bar)		V Viton		224NX01 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
		E 200 - 100 psi (7 - 14 bar)				224NX02 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
						912NX01 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						912NX02 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
						924NX01 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						924NX02 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver