



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Viton: 990-511-006
----------------------	--------------------

CONFIGURATION OPTIONS

Model Code Example: PRDPLMXDN

CONTROL	(M)	OPERATING RANGE	(D)	SEAL MATERIAL	(N)	BOBINA
M Manual Override (Standard)		D 50 - 485 psi (3,5 - 33,5 bar)		N Buna-N		No coil
E Twist (Extended) Manual Override		B 100 - 1125 psi (7 - 77,5 bar)		E EPDM		224NX01 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
L Standard Screw Adjustment		E 25 - 250 psi (1,7 - 18 bar)		V Viton		224NX02 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
X No Manual Override						912NX01 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						912NX02 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
						924NX01 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						924NX02 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver