



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	0.25 gpm
Maximum Valve Leakage at 110 SUS (24 cSt)	50 cc/min.
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

CONFIGURATION OPTIONS

Model Code Example: PRFRLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment	A	750 - 3000 psi (50 - 210 bar), 1000 psi (70 bar) Standard Setting	N	Buna-N		Standard Material/Coating
	E		E	EPDM	/AP	Stainless Steel, Passivated
	B	300 - 1500 psi (20 - 105 bar), 500 psi (35 bar) Standard Setting	V	Viton	/LH	Mild Steel, Zinc-Nickel
	D	200 - 800 psi (14 - 55 bar), 400 psi (28 bar) Standard Setting				
	E	100 - 400 psi (7 - 28 bar), 200 psi (14 bar) Standard Setting				
	S	50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar) Standard Setting				
	W	1000 - 4500 psi (70 - 315 bar), 1000 psi (70 bar) Standard Setting				