



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-17A
	3
	160 L/min.
	350 bar
110 SUS (24 cSt)	65 cc/min.
	0.25 gpm
-	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.71 kg.
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

OPTION SELECTION EXAMPLE: PRHRLAN

	(L)	(A)	(N)	MATERIAL/COATING
L	A	750 - 3000 psi (50 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
	B	300 - 1500 psi (20 - 105 bar), 500 psi (35 bar)	E	/AP
	D	200 - 800 psi (14 - 55 bar), 400 psi (28 bar)	V	/LH -
	E	100 - 400 psi (7 - 28 bar), 200 psi (14 bar)		
	S	50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar)		
	W	1100 - 4500 psi (76 - 315 bar), 1100 psi (76 bar)		

TECHNICAL FEATURES

-
- PR*R LP*C
- 1 2
- 5000 psi (350 bar)
-
-
- 3 1:1 5000 psi 350 bar
- 3 2000 psi (140 bar)
- Sun /

PERFORMANCE CURVES

