



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-19A
	4
	320 L/min.
	350 bar
110 SUS (24 cSt)	80 cc/min.
	0.25 gpm
-	5
	41,3 mm
	474 - 508 Nm
	4 mm
	15 mm
	9 - 10 Nm
	1.59 kg.
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	EPDM: 990-019-014
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006

# OPTION SELECTION EXAMPLE: PRJRLAN

	(L)	(A)	(N)	MATERIAL/COATING
<b>L</b>		<b>A</b> 750 - 3000 psi (50 - 210 bar), 1000 psi (70 bar)	<b>N</b>	Standard Material/Coating
<b>C</b>	-		<b>E</b> EPDM	<b>/AP</b>
<b>K</b>		<b>B</b> 300 - 1500 psi (20 - 105 bar), 500 psi (35 bar)	<b>V</b>	
		<b>D</b> 200 - 800 psi (14 - 55 bar), 400 psi (28 bar)		
		<b>E</b> 100 - 400 psi (7 - 28 bar), 200 psi (14 bar)		
		<b>S</b> 50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar)		
		<b>W</b> 1100 - 4500 psi (76 - 315 bar), 1100 psi (76 bar)		

## TECHNICAL FEATURES

- 
- PR\*R LP\*C
- EPDM
- 1 2
- 5000 psi (350 bar)
- 
- 
- 3 1:1 5000 psi 350 bar
- 3 2000 psi (140 bar)
- Sun /

## PERFORMANCE CURVES

