



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-21A
	1
	40 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min.@70 bar
	0.25 gpm
	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.19 kg.
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

: • 0                    1                    0.75 in. (19 mm)

# OPTION SELECTION EXAMPLE: PSDBLAN

	(L)	(A)	(N)	MATERIAL/COATING
<b>L</b>	<b>A</b>	<b>500 - 3000 psi (35 - 210 bar), 700 psi (50 bar)</b>	<b>N</b>	Standard Material/Coating
		<b>B</b>	<b>V</b>	/LH -
		<b>50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)</b>		
		<b>D</b>		
		<b>25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)</b>		
		<b>S</b>		
		<b>25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar)</b>		
		<b>W</b>		
		<b>750 - 4500 psi (50 - 315 bar), 1000 psi (70 bar)</b>		

## TECHNICAL FEATURES

- 3 3000 psi (210 bar)
- 5000 psi (350 bar)
- 
- 
- 
- 
- 5%
- 4 1:1 5000 psi 350 bar
- 3 2000 psi (140 bar)
- 1 2
- 4
- Sun /

## PERFORMANCE CURVES

