



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	41 cc/min.
Optimum Inlet Pressure	210 bar
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

CONFIGURATION OPTIONS

Model Code Example: PSDPMDN

CONTROL	(M)	OPERATING RANGE	(D)	SEAL MATERIAL	(N)	BOBINA	(212)
M Manual Override (Standard)		D 50 - 485 psi (3,5 - 33,5 bar)		N Buna-N		No Coil	
		B 100 - 1125 psi (7 - 77,5 bar)		V Viton		224NX01 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver	
		E 25 - 250 psi (1,7 - 18 bar)				224NX02 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver	
						912NX01 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver	
						912NX02 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver	
						924NX01 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver	
						924NX02 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver	