



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-22A
	2
	80 L/min.
	350 bar
110 SUS (24 cSt)	50 cc/min.@70 bar
	0.25 gpm
-	5
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.33 kg.
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

# OPTION SELECTION EXAMPLE: PSFBLAN

(L)

(A)

(N)

**L**

**A** 750 - 3000 psi (50 - 210 bar), 1000 psi (70 bar)

**N**

- B** 300 - 1500 psi (20 - 105 bar), 500 psi (35 bar)
- D** 200 - 800 psi (14 - 55 bar), 400 psi (28 bar)
- E** 100 - 400 psi (7 - 28 bar), 200 psi (14 bar)
- S** 50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar)

**V**

## TECHNICAL FEATURES

- 3 3000 psi (210 bar)
- 5000 psi (350 bar)
- 
- 
- 
- 5%
- 
- 4 1:1 5000 psi 350 bar
- 3 2000 psi (140 bar)
- 1 2
- 4
- Sun /

## PERFORMANCE CURVES

