



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-22A
Series	2
Capacity	80 L/min.
Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	blocked control port (dead headed)
Maximum Valve Leakage at 110 SUS (24 cSt)	50 cc/min.@70 bar
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Model Weight	0.30 kg.
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	EPDM: 990-022-014
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	EPDM: 990-022-014
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

# OPTION SELECTION EXAMPLE: PSFTXFN

CONTROL

(X) BIAS PRESSURE

(F) SEAL MATERIAL

(N)

X Not Adjustable

F 100 psi (7 bar)

N Buna-N

E EPDM

V Viton

## PERFORMANCE CURVES

