



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-22A
	2
	80 L/min.
	350 bar
110 SUS (24 cSt)	50 cc/min.@70 bar
	blocked control port (dead headed)
	28,6 mm
	61 - 68 Nm
	0.30 kg.
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	EPDM: 990-022-014
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	EPDM: 990-022-014
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

# OPTION SELECTION EXAMPLE: PSFTXFN

(X)

(F)

(N)

**X**

**F** 100 psi (7 bar)

**N**

E EPDM  
V

## TECHNICAL FEATURES

- 100 psi (7 bar) 4 4 1000 psi (70 bar) 1 900 psi (63 bar)
- 3 3000 psi (210 bar)
- 5000 psi (350 bar)
- 
- 
- 
- 4 1:1 5000 psi 350 bar
- 3 2000 psi (140 bar)
- EPDM
- 1 2
- Sun /

## PERFORMANCE CURVES

