



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-23A
Series	3
Capacity	160 L/min.
Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	0.25 gpm
Maximum Valve Leakage at 110 SUS (24 cSt)	65 cc/min. @70 bar
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.68 kg.
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

# OPTION SELECTION EXAMPLE: PSHBLAN

**CONTROL**

- L** Standard Screw Adjustment
- C** Tamper Resistant - Factory Set

**(L) ADJUSTMENT RANGE**

- A** 750 - 3000 psi (50 - 210 bar), 1000 psi (70 bar) Standard Setting
- B** 300 - 1500 psi (20 - 105 bar), 500 psi (35 bar) Standard Setting
- W** 1100 - 4500 psi (76 - 315 bar), 1100 psi (76 bar) Standard Setting

**(A) SEAL MATERIAL**

- N** Buna-N
- E** EPDM
- V** Viton

**(N)**

## PERFORMANCE CURVES

