



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-23A
	3
	160 L/min.
	350 bar
110 SUS (24 cSt)	65 cc/min.@70 bar
	0.25 gpm
-	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.68 kg.
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

OPTION SELECTION EXAMPLE: PSHBLAN

(L)

(A)

(N)

L	A 750 - 3000 psi (50 - 210 bar), 1000 psi (70 bar)
	B 300 - 1500 psi (20 - 105 bar), 500 psi (35 bar)
	D 200 - 800 psi (14 - 55 bar), 400 psi (28 bar)
	E 100 - 400 psi (7 - 28 bar), 200 psi (14 bar)
	S 50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar)
	W 1100 - 4500 psi (76 - 315 bar), 1100 psi (76 bar)

N
E EPDM
V

TECHNICAL FEATURES

- 3 3000 psi (210 bar)
- 5000 psi (350 bar)
-
-
- 5%
-
- 4 1:1 5000 psi 350 bar
- 3 2000 psi (140 bar)
- EPDM
- 1 2
- 4
- Sun /

PERFORMANCE CURVES

