



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-23A
	3
	160 L/min.
	350 bar
110 SUS (24 cSt)	65 cc/min. @70 bar
	blocked control port (dead headed)
	31,8 mm
	203 - 217 Nm
	0.62 kg.
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

OPTION SELECTION EXAMPLE: PSHTXFN

(X)

(F)

(N)

X

F 100 psi (7 bar)

N

E EPDM
V

TECHNICAL FEATURES

- 100 psi (7 bar) 4 1000 psi (70 bar) 1 900 psi (63 bar)
- 3 3000 psi (210 bar)
- 5000 psi (350 bar)
-
-
-
- 4 1:1 5000 psi 350 bar
- 3 2000 psi (140 bar)
- EPDM
- 1 2
- Sun /

PERFORMANCE CURVES

