



2 1 1 3 4 3

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	350 bar
	blocked control port (dead headed)
	0,11 - 0,16 L/min.
-	5
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	EPDM: 990-021-014
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	EPDM: 990-021-014
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

: • : A B 3000 psi (210 bar) D E 2000 psi (140 bar) W 5000 psi (350 bar)

CONFIGURATION OPTIONS

Model Code Example: PVDALNN

(L)	(N)	(N)	MATERIAL/COATING
L	N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	N	Standard Material/Coating
W	A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	V	/AP
	B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)		/LH -
	D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)		
	Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)		
	W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)		