



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-21A
Series	1
Capacity	40 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,11 - 0,16 L/min.
Factory Pressure Settings Established at	blocked control port (dead headed)
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.19 kg.
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	EPDM: 990-021-014
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

OPTION SELECTION EXAMPLE: PVDBLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
L		Standard Screw Adjustment		N		Standard Material/Coating
C		Tamper Resistant - Factory Set		V		/AP Stainless Steel, Passivated
		A				
		B				
		C				
		D				
		E				
		N				
		Q				
		W				

PERFORMANCE CURVES

