



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-21A
	1
	40 L/min.
	350 bar
	blocked control port (dead headed)
	0,11 - 0,16 L/min.
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.19 kg.
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	EPDM: 990-021-014
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	EPDM: 990-021-014
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

: • : A B 3000 psi (210 bar) D E 2000 psi (140 bar) W 5000 psi (350 bar)

OPTION SELECTION EXAMPLE: PVDBLNN

	(L)	(N)	(N)	MATERIAL/COATING
L	N	N	N	Standard Material/Coating
	60 - 800 psi (4 - 55 bar), 200 psi (14 bar) A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) C 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar) D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)	V	V	/AP

TECHNICAL FEATURES

- 3 1:1 3000 psi 210 bar
- EPDM
- 1 2
-
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- 4
- Sun /

PERFORMANCE CURVES

