



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| Seal kit - Cartridge | Buna: 990-022-007 |
| Seal kit - Cartridge | Polyurethane: 990-022-002 |
| Seal kit - Cartridge | Viton: 990-022-006 |

CONFIGURATION OPTIONS

Model Code Example: PVFALAN

| CONTROL | (L) | ADJUSTMENT RANGE | (A) | SEAL MATERIAL | (N) | MATERIAL/COATING |
|---|-----|---|-----|-----------------|-----|---------------------------------|
| L Standard Screw Adjustment | | A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting | | N Buna-N | | Standard Material/Coating |
| C Tamper Resistant - Factory Set | | B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting | | E EPDM | | /AP Stainless Steel, Passivated |
| W Hex Wrench Adjustment | | D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting | | V Viton | | /LH Mild Steel, Zinc-Nickel |
| Y manilla de tres agarres | | E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting | | | | |
| | | W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) Standard Setting | | | | |