



2 1 1 3 4 3

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-22A
	2
	80 L/min.
	350 bar
	blocked control port (dead headed)
	0,16 - 0,25 L/min.
-	5
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0,30 kg
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

: • : A B 3000 psi (210 bar) D E 2000 psi (140 bar) W 5000 psi (350 bar)

# OPTION SELECTION EXAMPLE: PVFALN

	(L)	(N)	MATERIAL/COATING
<b>L</b>	<b>N</b>	Standard Material/Coating	
W	E EPDM	/AP	
	V	/LH	-

## TECHNICAL FEATURES

- 3 3000 psi (210 bar)
- 
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- 4 5000 psi (350 bar)
- /
- 4 1:1 5000 psi 350 bar
- /
- W Y W Y
- 4
- Sun /

## PERFORMANCE CURVES

