



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--|------------------------------------|
| cavidad | T-22A |
| Series | 2 |
| Capacity | 80 L/min. |
| Maximum Operating Pressure | 350 bar |
| Control Pilot Flow | 0,16 - 0,25 L/min. |
| Factory Pressure Settings Established at | blocked control port (dead headed) |
| Adjustment - No. of CW Turns from Min. to Max. setting | 5 |
| Valve Hex Size | 28,6 mm |
| Valve Installation Torque | 61 - 68 Nm |
| Adjustment Screw Internal Hex Size | 4 mm |
| Locknut Hex Size | 15 mm |
| Locknut Torque | 9 - 10 Nm |
| Model Weight | 0.34 kg. |
| Seal kit - Cartridge | Buna: 990-022-007 |
| Seal kit - Cartridge | Polyurethane: 990-022-002 |
| Seal kit - Cartridge | Viton: 990-022-006 |
| Seal kit - Cartridge | Buna: 990-022-007 |
| Seal kit - Cartridge | Polyurethane: 990-022-002 |
| Seal kit - Cartridge | Viton: 990-022-006 |

OPTION SELECTION EXAMPLE: PVFBLAN

| CONTROL | (L) ADJUSTMENT RANGE | (A) SEAL MATERIAL | (N) MATERIAL/COATING |
|-----------------------------|---|-----------------------------------|---|
| L Standard Screw Adjustment | A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) Standard Setting | N Buna-N V Viton | Standard Material/Coating /AP Stainless Steel, Passivated |

PERFORMANCE CURVES

