



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

CONFIGURATION OPTIONS

Model Code Example: PVHALAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment		A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting		N Buna-N		Standard Material/Coating
C Tamper Resistant - Factory Set		B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting		E EPDM		/AP Stainless Steel, Passivated
		D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting		V Viton		
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				
		W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) Standard Setting				