



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-23A
	3
	160 L/min.
	350 bar
	blocked control port (dead headed)
	0,25 - 0,33 L/min.
	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.70 kg.
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	EPDM: 990-023-014
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

: • : A B 3000 psi (210 bar) D E 2000 psi (140 bar) W 5000 psi (350 bar)

OPTION SELECTION EXAMPLE: PVHBLAN

(L)	(A)	(N)	MATERIAL/COATING
L	<p>A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)</p> <p>B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)</p> <p>D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)</p> <p>W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)</p>	N V	<p>Standard Material/Coating</p> <p>/AP</p> <p>/LH</p>

TECHNICAL FEATURES

- 3 1:1 3000 psi 210 bar
- EPDM
- 1 2
-
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- 4
- Sun /

PERFORMANCE CURVES

